

Mapping API Response Handling

This documentation is no longer actively supported and may be out of date. Going forward, please visit and bookmark our new site (<https://docs.phunware.com/>) for up-to-date documentation.

HTTP Status Codes

Below is a detailed outline of the status codes and messages used in the API.

Status Code	Message	Description
200	Success	<ul style="list-style-type: none">Used for general success.Used when a POST operation results in the creation of a new resource (such that response should contain URI of newly created resource).
202	Accepted	<ul style="list-style-type: none">Used to indicate that the message has been received, but processing may not yet be finished.
204	No Content	<ul style="list-style-type: none">Used for success when there is no response body to return.
400	Bad Request	<ul style="list-style-type: none">Used when one or more parameters are invalid.Used when one or more required parameters are missing.Used when the JSON payload is not valid JSON.
401	Unauthorized	<ul style="list-style-type: none">Used when the operation fails authorization checks.
403	Forbidden	<ul style="list-style-type: none">Used when the operation fails security checks (e.g. wrong app ID specified as input to retrieve specific data).
404	Not Found	<ul style="list-style-type: none">Used when the requested resource does not exist (e.g. app ID).
406	Not Acceptable	<ul style="list-style-type: none">Used when the content type passed in the request is not 'application/json'.
423	Locked	<ul style="list-style-type: none">Used to indicate that the resources is locked, such as during a process that takes longer than typical http response times, like route reset operations.
500	Internal Server Error	<ul style="list-style-type: none">Used when the (internal) server is down.

ON THIS PAGE

- [HTTP Status Codes](#)
- [Error Payloads](#)
 - [400](#)
 - [401](#)
 - [403](#)
 - [404](#)
 - [406](#)
 - [423](#)
 - [500](#)

Error Payloads

Each failed response will include a JSON payload that includes the error code number and message:

400

The actual message for this "Bad Request" error will vary depending on whether the error was caused by bad data sent in the request, a validation error when validating the request data or any other generic request error.

```
{
  "error":
  {
    "code": 400,
    "message": <error string>
  }
}
```

401

The actual message for this "Unauthorized" error will vary. The error string below will be one of the following:

- "Missing X-Auth header."
- "Auth header contains <num> parts; must be 3."
- "The request time is too far in the future (<num> seconds)."
- "The request time is too far in the past (<num> seconds)."
- "Invalid access key."
- "This access key has not been activated yet."
- "Could not decrypt the request."
- "Invalid signature."

```
{
  "error":
  {
    "code": 401,
    "message": <error string>
  }
}
```

403

The actual message for this "Forbidden" error will vary.

```
{
  "error":
  {
    "code": 403,
    "message": <error string>
  }
}
```

404

The actual message for this "Not Found" error will vary depending on what could not be found.

```
{
  "error":
  {
    "code": 404,
    "message": <error string>
  }
}
```

406

The actual message for this "Not Acceptable" error will vary.

```
{
  "error":
  {
    "code": 406,
    "message": <error string>
  }
}
```

423

```
{
  "data":
  {
    "code": 423,
    "message": "Resource locked."
  }
}
```

500

```
{
  "data":
  {
    "code": 500,
    "message": "An unknown error occurred."
  }
}
```