

Delete a File 2.0

Delete a File

This method is used to delete files previously uploaded through the [upload](#) and [replace](#) endpoints.

Method

DELETE

URL

<https://cms-api.phunware.com/v2.0/file/s3>

Headers

In order to provide CME with the JWT, you must provide a header named Authorization and the token must be prefixed with the word Bearer.

Key	Authorization
Value	Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpZCI6MTY3NCwiZW1haWwiOiJvcmdvd25lckBjeWJhZ2UuY29tliwiZmlyc3RfcmFtZSI6IkN5YmFnZSIsImxhc3RfcmFtZSI6Ik9yZyBPd25lcklslm9yZ3MiOltldCJzZXNzaW9uX2lkIjoiNzk3ZWVjNmY2Mjk5Y2JmYmEyODE3NDIhMGFIZjI0YmNhNmZmODM0NSIsIm9yZ19pZCI6NTEslm9yZ19uYW1lIjoiQ3liYWdlIiEhNSZWFuIiwiaWF0IjoxNDg4MjI0ODY0LCJleHAiOiJlE0ODgzMTYyNjR9.Vd7BCYEkeWOq2B3_3Np9yYDwYaAWyE1-e4ZvClvK4E

Request

Parameters

Parameter	Value	Description
<u>file</u>	URL	An S3 URL returned from the upload or replace endpoint.

Required parameters are underlined.

Request

```
{
  "file":
  "https://lbs-dev.s3.amazonaws.com/cyb-cln/e4d22a023db54fa08680b11078e0d9d6/dog_typing_fast.gif"
}
```

Response

A successful response will have a 200 status code and a body containing the URL of the new file.

```
{
  "message": "Successfully deleted file from S3."
}
```

Error Handling

An error response will return a 400, 403, or 404 (or 500 for internal server error) and a message:

```
{  
  "message": "File does not exist."  
}
```